PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



A1 08/0193 01.07.98 G XAGEI dge Sci B).	BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HR, HU, ID, IL, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF,
08/0193 01.07.98 Gi XAGEI dge Sci B).	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HR, HU, ID, IL, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
GI XAGEI dge Sci B).	BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
B1 2A0	I, With international search report.
data f	I sequence is not the most efficient means of permanent storage. The or electronic storage by utilising a sub-byte datatype for the storage or age or a database. For nucleotide sequences, for example, 2 bits can be
	ansford

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazi)	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JΡ	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	u	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

BIOLOGICAL DATA

This invention relates to the compression of biological sequence data for electronic storage.

The nature of biological sequence data (eg. DNA and protein sequences) means that electronic storage is perfectly suited. Not only does the sheer volume of data necessitate large-scale 5 storage, but electronic storage allows rapid and efficient searching of the data eg. for homologous sequences. Since the advent of initiatives such as whole genome sequencing, the amount of storage required has increased significantly. The storage requirement for the yeast genome, for instance, is huge. Whilst large capacity storage systems continue to fall in price, one of the rate-limiting steps when dealing with sequence data is the transfer from storage 10 medium into memory (eg. hard drive into RAM) and any developments which significantly reduce the size of sequence data files would be welcomed.

Biological sequence data is typically represented in an alphabetic manner, rather than by chemical formula, with each letter representing a monomer unit in a biological polymer (Table I). For instance, DNA sequences are represented as strings of letters chosen from a simple 15 four-letter "alphabet". Each A, C, G or T represents a monomer unit (nucleotide) in a DNA polymer. Similarly, proteins are made up of twenty different monomer units (amino acids), which have each been assigned single letter codes.

Because of its alphabetic nature, biological sequence data is naturally suited to electronic storage in alphabetic text form. Alphabetic text-based computer information is generally stored and 20 manipulated using the *char* datatype, using 8 bits (1 byte) and a conventional file of biological sequence data is made up of a string of characters of datatype *char*. A conventional file of sequence data uses a single byte to represent each monomer, so the amino acid sequence of the glycogen synthase protein, for example, requires 737 bytes of storage using the one-letter amino acid code, and the corresponding DNA sequence requires 2211 bytes.

25 The char datatype, however, was designed for representing a full character set, including upper and lower case letters plus numbers, punctuation, and other characters, and each 8-bit char can represent 256 (28) different values. Using the char datatype and alphanumeric characters to store DNA sequences therefore fails to utilise 252 of the available values. Similarly, protein sequences waste 236 values. Other datatypes which are in common usage for data storage include int (16 30 bits), long (32 bits), float (32 bits), although this may vary from machine to machine.

The DNA and RNA alphabets each consist of 4 letters and, rather than storing these sequences in alphanumeric form-using strings of char-datatype, using a sub-byte-datatype-would-enable a significant storage saving. Degenerate nucleic acid sequence information (which can be represented using a 16 letter alphabet) and protein sequences could also be treated in this way. It would therefore be useful to define a sub-byte datatype in order to take advantage of the small size of the biological alphabet.

The commonly used *blast* sequence comparison program converts single byte *char* data into a half-byte working space whilst manipulating data. This is a temporary measure, however, and data is not stored in this manner using a specific sub-byte datatype.

10 The invention is based upon the realisation that using a whole byte to represent a monomer in a biological sequence is not the most efficient means of permanent storage.

According to the invention, there is defined a sub-byte datatype for the storage or manipulation of biological sequence data in a programming language or a database.

The invention also provides a programming language or a database which utilises a sub-byte datatype for the storage or manipulation of biological sequence data.

According to a further aspect of the invention, there is provided the use of a sub-byte datatype in the storage or manipulation of biological sequence data.

By "sub-byte" it is meant fewer than 8 bits.

The datatype may be intrinsic to a program or programming language, or it may be user-defined.

20 The invention is not limited, however, to situations where a formal datatype must be defined.

According to a further aspect of the invention, there is provided a computer program which stores biological sequence data using fewer than 8 bits to represent each monomer in said sequence data.

The invention also provides a file containing biological sequence data, wherein each monomer in said sequence data is represented using fewer than 8 bits.

According to a further aspect of the invention, there is provided a method for compressing biological sequence data, comprising representing each monomer in said sequence data by using

fewer than 8 bits.

The invention also provides a method for reducing the size of a file in which biological sequence data is represented using 8 or more bits per monomer, comprising replacing the representation of each monomer with a representation using fewer than 8 bits.

5 According to a further aspect of the invention, there is provided a computer programmed to store biological sequence data by using fewer than 8 bits to represent each monomer in said sequence data.

According to a further aspect of the invention, there is provided a computer comprising means for alphabetic entry of biological sequence data, means to convert said sequence data into a 10 format wherein each monomer unit is represented using fewer than 8 bits and, preferably, means to store said data.

According to a further aspect of the invention, there is provided a storage medium holding biological sequence data, wherein said sequence data is stored using fewer than 8 bits to represent each monomer in said sequence data.

15 The storage medium may be in any appropriate form, such as a floppy disk, a CD-ROM, or a fixed disk drive.

According to a further aspect of the invention, there is provided a method for transmitting biological sequence data, comprising compressing the data by representing each monomer in said sequence data by using fewer than 8 bits before transmission, for instance over a network.

20 According to a further aspect of the invention, there is provided biological sequence data which has been electronically stored using less than 8 bits to represent each monomer in said sequence data.

The biological sequence data may be of any suitable kind, such as DNA sequence, RNA sequence, and protein or polypeptide sequence.

25 It will be apparent that nucleic acid sequences can be represented using 2 bits to represent each monomer (nucleotides A, C, G, or T/U). Accordingly, a 2 bit datatype may be defined according to the invention for the storage or manipulation of nucleic acid sequences. Such a datatype is

referred to herein as base.

By representing each nucleotide in a nucleic acid sequence by using only 2 bits, 4 nucleotides can be stored in a single byte. This represents a 75% compression compared with the conventional representation of each nucleotide using a single byte.

5 Where a nucleic acid sequence is not definite, more than 2 bits are required to represent each nucleotide. For instance, where a nucleotide has not been unequivocally determined, the symbol "N" is used according to IUPAC convention. The alphabet of this IUPAC convention (Table I) has 16 members. This can be conveniently represented using 4 bits per member. Accordingly, a 4 bit datatype may be defined according to the invention for the storage or manipulation of 10 degenerate or uncertain nucleic acid sequences. Such a datatype is referred to herein as longbase.

By representing each nucleotide in a sequence by using 4 bits, 2 nucleotides can be stored in a single byte. This represents a 50% compression compared with the conventional representation of each nucleotide using a single byte.

As an alternative to using 4 bits to represent degenerate or uncertain nucleic acid sequences, 15 under certain circumstances these features may be accommodated where 2 bits are used, as in base. For instance, where a DNA sequence is stored in a data file using 2 bits per nucleotide, parallel files could be utilised which contain "modifying" data to qualify details in the sequence file. For instance, the second file may contain an indication that whilst nucleotide 221 is given as guanine in the sequence file, in fact it may be any purine. Obviously, the choice of using such a 20 "modifying" file or using more than 2 bits to represent the sequence depends on the particular situation, but the choice is routine.

It will further be apparent that protein sequences require at least 5 bits to represent each monomer (20 amino acids) since 2⁴=16 and 2⁵=32. Whilst this is encompassed within the invention, 5 bits is an awkward length, being an odd number. 6 bits is more convenient and, furthermore, this allows a degree of degeneracy to be incorporated into the sequence (2⁶=64). Accordingly, a 6 bit datatype may be defined according to the invention for the storage or manipulation of protein sequences. Such a datatype is referred to herein as aminoacid.

By representing each amino acid in a protein sequence by using 6 bits, 4 amino acids can be stored in 3 bytes. This represents a 25% compression compared with the conventional

representation of each amino acid using a single byte.

The degree of degeneracy incorporated into a 6-bit representation or datatype also allows an amino acid to be represented in terms of codons, of which there are 64. A datatype used in this way is referred to herein as *codon*. Each single *codon* value represents a single codon, which 5 inherently also defines an amino acid. In effect, the *codon* datatype represents three *base* entries, just as a codon is made up of three nucleotides. By using 6 bits to represent each codon, 4 codons can be represented in 3 bytes. This represents a 75% compression compared with the conventional representation of each codon using 3 bytes. It will also be appreciated that a full byte could be used to represent each codon, which would allow a degree of degeneracy and 10 would represent a 67% compression compared with using 3 bytes to represent each codon.

It should be borne in mind that the various datatypes and compressions described above may not be suitable in all circumstances. For example, the programming language C requires a string to have a NULL terminator. This is not possible with the *base* datatype, for instance, because all of the 4 possible values (permutations of 2 bits) are used to represent information, which does not 15 allow a terminator to be represented.

Similar caveats apply to *longbase*. The IUPAC convention uses 15 representations for a DNA or RNA sequence, which does allow the sixteenth permutation to represent a terminator. In certain circumstances, however, a value may be needed to represent a gap (representing an unknown sequence of unknown length) which would remove the possibility of having a terminator. The 20 *codon* datatype is also "full" since each of the 64 available values represents a codon.

Whilst these datatypes may not be universally applicable, however, they are not without utility since not all programming languages or databases have such a terminator requirement. A further problem in using the datatypes of the invention in languages such as C is the international ANSI standard which does not recognise these datatypes. However, new languages, such as Java which 25 is still in early development, currently have less strict standards and may be amenable to the introduction of new datatypes at this stage.

TABLE I

-IUB/IUPAC-standard-biological-sequence-codes-

Single letter nucleotide codes

- A Adenine
- C Cytosine
- 5 G Guanine
- T Thymine
- U Uracil

Degenerate nucleotide codes

In addition to the five above codes:

- N any (A/C/G/T)
- R puRine (G/A)
- y pYrimidine (T/C)

- 10 K Keto (G/T)
- M aMino (A/C)
- S Strong (G/C)

- W Weak (A/T)
- B not A (C/G/T)
- D not C(A/G/T)

- H not G (A/C/T)
- $V \quad \text{not } T (A/C/G)$

Single letter amino acid codes

- A Alanine
- Cysteine
- D Aspartate

- 15 E Glutamate
- F Phenylalanine
- G Glycine

- H Histidine
- I Isoleucine
- K Lysine

- L Leucine
- M Methionine
- N Asparagine

- P Proline
- Q Glutamine
- R Arginine

Serine

- T Threonine
- v Valine

- 20 W Tryptophan
- Y Tyrosine

In addition:

S

- B represents asparagine or aspartate ie. N or D
- Z represents glutamine or glutamate ie. Q or E
- U represents selenocysteine
- 25 x represents "any amino acid" or "unknown"
 - * represents a translation stop
 - represents a gap of indeterminate length

CLAIMS

- 1. A sub-byte datatype for the storage or manipulation of biological sequence data in a programming language or a database.
- 2. A programming language or a database which utilises a sub-byte datatype for the storage or 5 manipulation of biological sequence data.
 - 3. The use of a sub-byte datatype in the storage or manipulation of biological sequence data.
 - 4. A file containing biological sequence data, wherein each monomer in said sequence data is represented using fewer than 8 bits.
- 5. A method for compressing biological sequence data, comprising representing each monomer 10 in said sequence data by using fewer than 8 bits.
 - 6. A method for reducing the size of a file in which biological sequence data is represented using 8 or more bits per monomer, comprising replacing the representation of each monomer with a representation using fewer than 8 bits.
- 7. A computer programmed to store biological sequence data by using fewer than 8 bits to 15 represent each monomer in said sequence data.
 - 8. A storage medium holding biological sequence data, wherein said sequence data is stored using fewer than 8 bits to represent each monomer in said sequence data.
 - 9. Biological sequence data which has been electronically stored using less than 8 bits to represent each monomer in said sequence data.

INTERNATIONAL SEARCH REPORT

In Alional Application No PCT/GB 98/01937

	<u> </u>			
A. CLASSI IPC 6	FICATION OF SUBJECT MATTER H03M7/30			
According to	o International Patent Classification (IPC) or to both national class	sification and IPC		
	SEARCHED			
	ocumentation searched (classification system followed by classifi H03M	cation symbols)		
Documentat	tion searched other than minimumdocumentation to the extent th	at such documents are included in the fields se	arched	
Electronic d	lata base consulted during the international search (name of data	a base and, where practical, search terms used)	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT			
Category ³	Citation of document, with indication, where appropriate, of the	relevant passages	Relevant to claim No.	
Ρ,Χ	WO 97 31327 A (MOTOROLA INC ;RI L (US); PERTTUNEN CARY D (US)) 28 August 1997 see page 5, line 21 - line 24	1-9		
Α	US 4 701 744 A (DEVILBISS WARR 20 October 1987 see the whole document	EN C)	1	
		:		
Furti	her documents are listed in the continuation of box C.	Patent family members are listed	in annex.	
"A" docume consider the consideration of th	ent which may throw doubte on priority claim(s) or is cited to establish the publication date of another in or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means ent published prior to the international filing date but han the priority date claimed	"T" later document published after the interest or priority date and not in conflict with cited to understand the principle or the invention. "X" document of particular relevance; the cannot be considered novel or cannor involve an inventive step when the decument of particular relevance; the cannot be considered to involve an indocument is combined with one or ments, such combination being obvious in the art. "&" document member of the same patent.	n the application but neary underlying the claimed invention is be considered to coursent is taken alone claimed invention nventive step when the core other such docupous to a person skilled it family	
	actual completion of theinternational search 9 September 1998	Date of mailing of the international sea	arch report	
	mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,	Authorized officer Feuer, F		

INTERNATIONAL SEARCH REPORT

tn. ittonal Application No
PCT/GB 98/01937

Patent document cited in search report	t	Publication date		Patent family member(s)	Publication date
WO_9.731327	A	28-08-1997	AU	1414197 A	10-09-1997
US 4701744	Α	20-10-1987	 AU	602512 B	18-10-1990
			AU	7046387 A	01-10-1987
			CA	1283483 A	23-04-1991
			DE	3787985 D	09-12-1993
			DE	3787985 T	19-05-1994
			EΡ	0240242 A	07-10-1987
		•	FΙ	871243 A,B,	28-09-1987
			JP	62237496 A	17-10-1987
	•	KR	9513258 B	26-10-1995	